

The Style You Like for The Home You Love

When arriving home, Laforge wants you to be greeted by a door that is not only safe and strong, a door that operates as it should. Why settle for anything less? We simply call it quality of life.

At Laforge Doors Ltd., we are committed to giving you peace of mind.



1 Polyurethane injected (CFC free) insulation ensures the panel's strength and provides an R-16 thermal value.



2 Wood end pieces ensure solidity and eliminate conduction of cold.



Aluminum bottom rail with an EPDM U-shaped flexible rubber provides a contoured seal between the door and the floor for maximum protection.



4 Designed and manufactured for harsh weather, our 4 point seal system creates a continuous barrier for each panel section.



Available in 6 different colors, the PVC side seals with double lip construction prevents air, snow and dust infiltration. Concealed fastener system for added beauty.



6 Fastened overlay boards are of cellular PVC construction.





PO Box 7849 FORGE Grand Falls, NB Van Buren, Maine E3Z 3E8 1-800-665-3667 (Canada/USA/Mexico)

Canada

USA

PO Box 417

USA 04785

www.laforgedoors.com







1. Choose your style and features.

1 3/4" steel; polyurethane injected insulation with an R-16 value; choice of 5 exotic colors; 2" steel heavy duty rollers; aluminum bottom rail; 10,000 cycles torsion spring; 21T commercial tracks.

The *Country Style* door is a unique and upmarket model. Manufactured with a superior quality steel, it requires minimal maintenance and exceeds the standards in the industry. This door is amongst our most energy efficiant and homeowners will be seduced by the variety of antique inspired models they can choose from.

handles

(included with Country Style)

For more information, contact your Laforge door dealer or go to www.laforgedoors.com.

Country Style doors are offered with a variety of decorative hardware.



Colonial hinges (1/4" thickness) (included with Country Style)



(optional)



Colonial Rustic handles (optional)

Colonial Knockers (optional)



